

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
22 September 2005 (22.09.2005)

PCT

(10) International Publication Number
WO 2005/088627 A1

(51) International Patent Classification⁷: **G11B 7/24**

(21) International Application Number:
PCT/JP2005/004893

(22) International Filing Date: 14 March 2005 (14.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2004-073829 16 March 2004 (16.03.2004) JP
2004-272411 17 September 2004 (17.09.2004) JP

(71) Applicant (for all designated States except US): **RICOH COMPANY, LTD.** [JP/JP]; 3-6, Nakamagome 1-chome, Ohta-ku, Tokyo, 1438555 (JP).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **ISHIMI, Tomomi** [JP/JP]; 2-9-5, Katsuradainami, Sakae-ku, Yokohama-shi, Kanagawa, 2470033 (JP).

(74) Agent: **HIROTA, Koichi**; HIROTA, NAGARE & ASSOCIATES, 8th Floor, Miyata Bldg., 1-38-2, Yoyogi, Shibuya-ku, Tokyo, 1510053 (JP).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: OPTICAL RECORDING MEDIUM

(57) Abstract: The optical recording medium according to the present invention comprises a transparent substrate, a recording layer, an optical reflective layer, and a protective layer, wherein the last three layers mentioned are formed on the substrate in this sequence, and enables recoding at a recording linear velocity of 27.9m/s or more. The optical reflective layer is characterized in that the layer comprises any one of Ag and an alloy mainly made from Ag and a x-ray diffraction spectrum of the optical reflective layer satisfies the relational expression of $0.2 < I(200) / I(111) < 0.4$, in which $I(111)$ is an intensity of the x-ray diffraction peak



WO 2005/088627 A1